


Maintenance

Silicone spray for Goelst systems

General

Goelst is known for its smooth running systems. To maintain a smooth running system, it is advised to lubricate Goelst aluminium profiles once a year. Goelst offers top quality lubricant: Silicone spray for Goelst curtain rail. This spray can be used on all Goelst rail systems and has a special nozzle. Spray a light dose on the profile's inner surfaces: as a guideline, spray along 10cm every 50cm.

Note: Use the spray moderately.



Spray along 10cm every 50cm,
with special nozzle.




Goelst Silicone Spray

The profile's outer surfaces can be cleaned using a soft cloth and a non abrasive cleaning agent. Use a vacuumcleaner to remove dust and loose particles from inner running surfaces.

Electrically operated systems


Pouly motor side:

At the point where the belt enters the pouly: spray during ~2 seconds. Spray in a running system, this will distribute the lubricant throughout the pouly.



Pouly return side:

At the point where the belt enters the pouly: spray during ~2 seconds. Spray in a running system, this will distribute the lubricant throughout the pouly.



Notes

- > Excessive use might cause the sprayed liquid to leak onto the curtains. This may stain or damage the curtains.
- > Excessive use of spray in an electrically operated system may cause the toothed belt to undergo extra resistance due to a sticking effect. This will have a negative effect on the system's performance or even cause damage.
- > Prevent excessive use of spray in a cord operated system, to keep the cord cleaner and make it less likely to collect filth.